



L-15 Laminating Adhesive

Product Application & Description

L-15 is a low odor foil laminating adhesive with an excellent adhesion to foil. The dried film has very good heat, water and toluol resistance. The initial tack, machining and stability characteristics are superior to most synthetic copolymer and casein foil laminates.

Shelf Life & Storage

It is recommended to consume all materials within 2 months from date of purchase. Best if stored in a controlled environment (72°F and 50% RH) and out of direct sunlight.

Technical Data	
Type	Synthetic Latex
Viscosity @ 75°F (24°C)	100 to 300 CPS
Solids	43% to 47%
pH	7.0 to 9.0
Running Temperature	59°F to 86°F (15°C to 30°C)
Water Resistance	Excellent

Please Note: The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.

16100 Imperial Parkway, Strongsville, OH 44149
1.800.521.0054 • info@allfoils.com