

## L-21 Laminating Adhesive

## Product Application & Description

L-21 is a premium laminating adhesive designed for us as an adhesive for bonding films and foils used for flexible packaging, solar films and other industrial laminations. L-21 weathers well and bonds to many surfaces including polyolefins, thermoplastics, various metal foils and cloth to name a few.

## Shelf Life & Storage

It is recommended to consume all materials within 1 year from date of purchase. Best if stored in a controlled environment (72°F and 50% RH) and out of direct sunlight. Temperatures must not exceed 80°F.

Technical Data	
Туре	Saturated Polyester
Viscosity @ 75°F (24°C)	960 CPS
Solids	45%
Weight/Gallon	7.9 lbs.
Temperature Range	55°F to 250°F (10°C to 121°C)
Specific Gravity	.952

**Please Note:** The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.