



L-22 Laminating Adhesive

Product Application & Description

L-22 is a high-performance polyester urethane laminating adhesive for film/film, film/aluminum and aluminum/electronics insulating paper laminations. L-22 provides heat and chemical resistance for technical laminations and is suitable for sterilization and deep-drawn applications.

Pot Life & Storage

Approximately 12 hours at ambient temperature if diluted. It is also recommended to mix with fresh solution before using. Humidity will negatively influence the pot life.

Shelf Life & Storage

It is recommended to consume adhesive within 12 months and hardener within 6 months from date of purchase when they are stored in unopened, original containers between 41°F and 95°F.

Technical Data

Max Service Temperature	450°F (Minimum of 5 Hours)
<i>Service temperature will vary based on the film/aluminum combinations of the laminate.</i>	

Please Note: The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.

16100 Imperial Parkway, Strongsville, OH 44149
1.800.521.0054 • info@allfoils.com